

Automatic Transfer Switch Specification

Date: 2023-12-01

No: CLAT0311810042

Product name		Factory Part No.		Brand			
STS/ATS		WB-ST5-6*C13+2*C19		WebIT			
Main Functions		Details					
Access method		Serial (Control console: Hyper Terminal)					
Local display and monitor via control console		Total load current					
		Input voltage					
		Status of Power supply Line A/B					
Control and configure via control console		Set ATS System clock					
		Set the threshold of current & voltage					
		Set the preferred power source					
		Set switch over time					
Alarm	User defined	Threshold of total load current					
		Threshold of input voltage					
	System default	When threshold of total load current is exceeded					
		When threshold of input voltage is exceeded					
		When either power supply goes wrong					
		When automatic switch happens					
	Alarm method	Audible and visual alarm (external connection)					
Input/output characteristics							
Input characteristics		Rated input voltage	220~250VAC 50-60Hz				
		Input standard	IEC 320 C20 socket (2pcs)				
		Cable specification	3×1.5mm ² with C19/ BS1363 13A plug 2pcs				
		Cable length	3M				
		Max. input current	16A				
Output characteristics		Socket standard	IEC 320 C13	Rated current	10A	Outlet quantity	6
			IEC 320 C19	Rated current	16A	Outlet quantity	2
		Rated output voltage	220V				
Dimension	Product dimension	L×W×H = 482.6×220×44.4mm					
Product drawing on next page							

ATS drawing

Front



Rear



C19/BS1363 16A plug with 3×1.5mm²×3M cable (2Pcs)

Design:	Customer confirm:	Check:	Approve:
---------	-------------------	--------	----------